	Description WALL EINISHES	Quantity	Units	Rate	Total
	WALL FINISHES M50 RUBBER/PLASTIC/CORK/LINO/CARPET				
	TILING/SHEETING				
	Soft padded wall mats covered with wipeable, non absorbent material. Suitable for 'robust				
	play'. Surface spread of flame rating required:				
	Class 3 or better. Walls				
A	Over 300 wide; R-017 Soft Play	48	m2		0.00
	FLOOR FINISHES PRELIMINARIES / GENERAL CONDITIONS				
	Notes				
В	Measurement note Allow for any necessary expansion		m	25.00	0.00
	details/joints to suit the current layout as				
	required by the manufacturers.  Allow for any necessary samples and spare		Box	61.00	0.00
	tiles etc at completion				
	M50 RUBBER/PLASTIC/CORK/LINO/CARPET TILING/SHEETING				
	Heavy Duty Recessed Barrier matting,				
	proprietary barrier carpet sheet, to be compliant with part M requirements				
	(M50:178A)				
)	Floors JHS Zermatt entrance matting Over 300 wide	68	m2	18.32	1,245.76
	Carpet tiling, Burmatex - Tivoli Multiline	00	2	10.02	1,243.70
	proprietary carpet tiles, fixing with adhesive colours as per Kier drawing 8520 Rev				
	C01(M50:130A)				
	Floors Over 300 wide	405		17.65	0.500.35
	Over 300 wide, in staircase areas	485 51	m2 m2	17.65 17.65	8,560.25 900.15
	Landings	^	m?	17.00	150.05
3	Over 300 wide Treads	9	m2	17.65	158.85
4	300 wide	75	m	6.22	466.50
:	Risers 160 high (assumed)	84	m	6.22	522.48
К	<u> </u>				
	Tanking, Cold applied damp proofing,				
	modified epoxide coating, 2 coats with				
	reinforcement as required by manufacturer, installed in accordance with manufacturers				
	requirements (J30:130)				
	Floors Over 300 wide; horizontal	59	m2		0.00
VI	Skirting; 300mm high; including angle fillet	56			0.00
	former; vertical Vinyl sheeting- Tarkett Safetred Wood				
	(Traditional Oak Grey) ,Non slip, proprietary				
	non slip vinyl flooring installed in accordance with manufacturers requirements (M50:150B)				
	with manufacturers requirements (WSS.1505)				
N	Floors Over 300 wide	307	m2	22.14	6,796.98
)	Extra for acoustic resiliant underlay		m2	3.45	138.00
	achieving minimum impact noise reduction				
	Treads				
•	300 wide Risers	10	m	11.34	113.40
Q	160 high (assumed)	12	m	11.34	136.08
-	Vinyl sheeting- Tarkett Safetred Universal				
	(Venus) Hydrotherapy pool, proprietary non				
	slip vinyl flooring installed in accordance with				
	manufacturers requirements (M50:150D)				
	Floors	403	2	20.74	2 426 22
₹	Over 300 wide  Skirtings, including all cove formers, ends,	103	1112	20.74	2,136.22
	angles and cappings				
5	100 high (assumed) Vinyl sheeting- Tarkett Safetred Universal	128	m	13.46	1,722.88
	(Venus) Server room, proprietary anti-static				
	vinyl flooring installed in accordance with manufacturers requirements (M50:150E)				
	Floors				
	Over 300 wide Extra for acoustic resiliant underlay	7 7	m2 m2	20.74 6.31	145.18 44.17
1		/	1112	6.31	44.1/
J	achieving minimum impact noise reduction				
J	achieving minimum impact noise reduction 15db				
J					
U	15db  Vinyl sheeting - Tarkett Safetred Universal				
J	15db  Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip,				
U	15db  Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements				
	15db  Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (M50:150F)	20	m2	20.74	414.80
	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MSO:150F)  Over 300 wide Skirtings, including all cove formers, ends,	20	m2	20.74	414.80
V	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MS0:150F) Over 300 wide Skirtings, including all cove formers, ends, angles and cappings				
V	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MSO:150F) Over 300 wide Skirtings, including all cove formers, ends, angles and cappings 100 high (assumed) Vinyl sheeting-Tarkett OmniSport Compact	20		20.74	414.80 215.36
V	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MS0:150F) Over 300 wide Skirtings, including all cove formers, ends, angles and cappings 100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable				
V	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MSO:150F) Over 300 wide Skirtings, including all cove formers, ends, angles and cappings 100 high (assumed) Vinyl sheeting-Tarkett OmniSport Compact				
V	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MS0:150F) Over 300 wide Skirtings, including all cove formers, ends, angles and cappings 100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable vinyl, suitable for sports hall/dining hall use installed in accordance with manufacturers requirements (M50:150G)				
v	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MS0:150F)  Over 300 wide Skirtings, including all cove formers, ends, angles and cappings  100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable vinyl, suitable for sports hall/dining hall use installed in accordance with manufacturers		m		
v N	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (M50:150F) Over 300 wide Skirtings, including all cove formers, ends, angles and cappings 100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable vinyl, suitable for sports hall/dining hall use installed in accordance with manufacturers requirements (M50:150G) Floors Over 300 wide Vinyl sheeting- Tarkett Safetred Wood	16	m	13.46	215.36
v N	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (M50:150F)  Over 300 wide Skirtings, including all cove formers, ends, angles and cappings  100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable vinyl, suitable for sports hall/dining hall use installed in accordance with manufacturers requirements (M50:150G) Floors  Over 300 wide Vinyl sheeting- Tarkett Safetred Wood (Traditional Oak Grey), proprietary non-slip	16	m	13.46	215.36
v N	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (M50:150F) Over 300 wide Skirtings, including all cove formers, ends, angles and cappings 100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable vinyl, suitable for sports hall/dining hall use installed in accordance with manufacturers requirements (M50:150G) Floors Over 300 wide Vinyl sheeting- Tarkett Safetred Wood (Traditional Oak Grey), proprietary non-slip vinyl flooring installed in accordance with manufacturers requirements (M50:150A)	16	m	13.46	215.36
v w	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MS0:150F)  Over 300 wide Skirtings, including all cove formers, ends, angles and cappings  100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable vinyl, suitable for sports hall/dining hall use installed in accordance with manufacturers requirements (MS0:150G) Floors  Over 300 wide Vinyl sheeting- Tarkett Safetred Wood (Traditional Oak Grey), proprietary non-slip vinyl flooring installed in accordance with manufacturers requirements (MS0:150A) Floors	16 260	m m2	13.46 23.87	215.36 6,206.20
v w x	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (M50:150F) Over 300 wide Skirtings, including all cove formers, ends, angles and cappings 100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable vinyl, suitable for sports hall/dining hall use installed in accordance with manufacturers requirements (M50:150G) Floors Over 300 wide Vinyl sheeting- Tarkett Safetred Wood (Traditional Oak Grey), proprietary non-slip vinyl flooring installed in accordance with manufacturers requirements (M50:150A)	16	m m2	13.46	215.36
V V W X X X Y Z Z	Vinyl sheeting - Tarkett Safetred Universal (Venus) Servery room, proprietary non-slip, anti-static vinyl flooring installed in accordance with manufacturers requirements (MS0:150F)  Over 300 wide Skirtings, including all cove formers, ends, angles and cappings  100 high (assumed) Vinyl sheeting- Tarkett OmniSport Compact (Oak Classic) Multipurpose non slip durable vinyl, suitable for sports hall/dining hall use installed in accordance with manufacturers requirements (M50:150G) Floors  Over 300 wide Vinyl sheeting- Tarkett Safetred Wood (Traditional Oak Grey), proprietary non-slip vinyl flooring installed in accordance with manufacturers requirements (M50:150A) Floors  Over 300 wide	16 260 975	m m2	23.87 22.14	215.36 6,206.20 21,586.50

	Vinyl sheeting- Tarkett Safetred Universal (Venus)Proprietary non-slip vinyl flooring installed in accordance with manufacturers requirements (M50:150C) Floors				
AA AB	Over 300 wide Extra for acoustic resiliant underlay achieving minimum impact noise reduction	305 27	m2 m2	20.74 6.31	6,325.70 170.37
	15db Skirtings, including all cove formers, ends, angles and cappings				
AC	100 high (assumed)  Vinyl sheeting- Tarkett Safetred Universal	88	m2	13.46	1,184.48
	(Venus) Proprietary non-slip vinyl flooring to wet areas installed in accordance with manufacturers requirements (M50:150H)				
AD AE	Over 300 wide Extra for acoustic resiliant underlay achieving minimum impact noise reduction 15db	122 13	m2 m2	20.74 6.31	2,530.28 82.03
AF	Skirtings, including all cove formers, ends, angles and cappings 100 high (assumed)	175	m2	13.46	2,355.50
AG	Threshold Division Strips  Multip purpose transition strip between	104	m	8.00	832.00
	carpet & vinyl floor finishes and barrier mat & vinyl floor finishes. Standard Aluminium Colour				
АН	Tremco SX302; nominal 3mm thick To floors; exc 300	2773	m2	4.46	Rate Only
AK	Tremco eS600 DPM (up to 95%) To Floors; exc 300mm Correx sheeting; flame-retardent; joint taped	2773	m2	6.11	Rate Only
AL	; 2mm thick To floors ; including later removal and disposal	2773	m2	1.70	Rate Only
	N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT Proprietary stair nosings, to be Part M and				
AM	equality act compliant (L30:590)  Quantum HF153 nosings  Preliminaries and Attendances to the above works	84	m	19.51	1,638.84
1	Please allow the following within your rates generally or as priced items below:  Site management; include for working	1	Item	Inc	
	supervisor , qualified to SSSTS/SMSTS and SEATS as minimum - additional duties of the supervisor shall include, but not be				
	limited to; Daily Start Right meetings; Weekly Collaborative Planning meetings;Weekly Tool Box Talks; Daily				
	Permits; Inspection of tools and equipment as necessary; Weekly progress reports; Weekly progress meetings; Compliant fieldview usage.				
2	Include for testing to floors to ensure correct relative humidity prior to application	1	Item	Inc	
3	Allow for preparation of floors prior to application			Site assesment required	
4	level/flatness/condition etc prior to works commencing in order to accept floors and	1	Item	Inc	
5	take responsibility from the point of acceptance Include for removal of all site waste and packaging associated with your works to	1	Item	Inc	
6	skips provided by the main contractor.	1	Item	Inc	
7	distribution of materials Allow for all sequences, visits and durations as set out in the C.9 programme	1	item	Inc	
Total	amplification				67,508.710